



# Commercial Series

	W25	LoPro	Whisper	C	CH	CHS
	<b>Recommended Maximum Mounting Height (Feet)</b>					
Environmental Separation	5'	8'			10'	12'
Insect Control	5'	7'			8'	10'
Drive Up / Concession	•	•	•			
Customer Entry		•	•	•		
Service Door					•	•
Shipping/Receiving					•	•
Freezer/Cooler Door		•	•	•	•	•
Strip Curtain Replacement						
Door to Patio		•	•	•		
Standard lengths (inches)	25"	30"-144"	36"-72"	36"-96"	36"-96"	36"-96"
Heat Options						
Unheated	•	•	•	•	•	•
Electric	•	•	•	•	•	•
Steam/Hot Water		•				

# Industrial Series

	Standard	HV	EP	Wind Stopping (Direct Drive)	Windguard (Belt Drive)
	<b>Recommended Maximum Mounting Height (Feet)</b>				
Environmental Separation	10'	12'	17'	16'	upto 30'
Insect Control	8'	10'	16'		
Commerical Entry	•	•			
Freezer/Cooler Door	•	•	•		
Service Door	•	•			
Shipping/Receiving	•	•	•	•	•
Automotive/Cargo		•	•	•	•
Standard lengths (inches)	36"-144"	42"-144"	48"-144"	48"-192"	96"-192"
Heat Options					
Unheated	•	•	•	•	•
Electric	•	•	•	•	•
Steam/Hot Water	•	•	•	•	•
Indirect Gas Fired		•	•	•	•
Direct Gas Fired				•	